



SPECIFICATIONS:

Low voltage adjustable recessed downlight with nominal 4" diameter trim and 1 5/8" diameter aperture.

Trim

- Precision machined, triple ring construction.
- Aluminum base material for painted finishes: White, Black, Metallic Silver.
- Brass base material for plated finishes: Polished Brass, Chrome, Matte Aluminum, Black Nickel.
- Rotating center ring pivots 30 degrees in either direction, capable of utilizing two (2) media accessories in conjunction with one MR16.
- Snap-in / Pull-out center ring assembly provides convenient servicing.

Electrical:

- Socket assembly (ceramic socket and wire lead) snaps directly to lamp pins. Socket assembly supplied with pre-wired rough-in housing. Rough-in ordered separately

Lamping:

- Enclosed MR16, 12volt or open MR16, 12 volt lamp with protective glass lens. 50 watt maximum for non-IC rated rough-in and 35 watt maximum for IC rated rough-in. Lamp provided by others.

Compliances:

- UL and cUL Listed when specified with appropriate A35 Series Rough-in housing. Suitable for use in damp locations.

Ordering Information

Part Number	Color: Plated Finish
DL21WH	White
DL21BK	Black
DL21MS	Metallic Silver

Part Number	Color: Plated Finish
DL21PB	Polished Brass
DL21PC	Polished Chrome
DL21MA	Matte Aluminum
DL21BN	Black Nickel

Use with A35 Series rough-in

Ardee Lighting reserves the right to change product specifications without prior notification.

Ardee Lighting			
3/5/2008	PO Box 1769 · 639 Washburn Switch Rd · Shelby · NC 28151 T 704. 482.2811 F 800.275.1544 E ardee@jjishelby.com www.ardeelighting.com	022045	